



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Belt Dressing & Conditioner

AAM Revised 10/02

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Belt Dressing is a specially formulated, high quality belt dressing that is designed to eliminate squeaks, aid in power transfer and increase belt life. The product penetrates the cord fibers to restore pliability and flexibility. Prevents belt slippage due to heat, cold, dampness, dust and glazing.

PRODUCT BENEFITS

- Increase pulling power of belt
- Protects belt from deterioration due to oxidation and heat
- Remains soft, does not harden or glaze
- Easy application, aerosol spray for maximum coverage, extension tube for hard to reach areas
- VOC compliant

TYPICAL APPLICATIONS


- V-belts or flat belts of rubber, leather or fabric
- Automotive
- Farm equipment
- Industrial belt drives

Note: Not recommended for use on serpentine belts

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
3. Attach extension tube
4. While engine is running, spray lightly on inner working surface of belt near smallest or uppermost pulley. Allow belt to run for several minutes to condition and cure dressing. Reapply as needed.

Note: Do not come in contact with moving parts.



5. Do not apply in excess, a uniform, thin coat is sufficient. If the liquid runs off, it indicates an over-application

Note: Prolonged or recurring squeaking is an indication that

the belt should be replaced due to excessive wear and deterioration.

For Cleanup

1. Turn can upside-down and spray to clear nozzle.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Rubber
Appearance	Clear liquid
Odor	Solvent
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly flammable)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80073 (120DA)	12 oz. net aerosol can
80074 (120GA)	5 oz. net aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX)